

EcoSolvent™ ETI-927

MATERIAL SAFETY DATA SHEET

CHEMTREC: 800-424-9300

SECTION 1-IDENTIFICATION

PRODUCT: **ECOSOLVENT™**
Product Number: ETI-927

Supplier: **EnvTech, Inc.™ (ETI)**
8263 Alpine Avenue
Sacramento, CA. 95826
1-877-841-9690
(916) 455-9690

SECTION 2-HEALTH INFORMATION

EFFECTS OF OVEREXPOSURE

INHALATION: No known problems.
INGESTION: LD50:>50ml/kg (albino rats)(similar products)
EYE CONTACT: Not classified as eye irritants.
SKIN CONTACT: Not classified as a skin irritant or corrosive material.

SECTION 3-OCCUPATIONAL EXPOSURE LIMITS

PEL: NO OSHA PEL TLV: NO ACGIH TLV

SECTION 4-EMERGENCY FIRST AID PROCEDURE

FOLLOW STANDARD FIRST AID PROCEDURES

SWALLOWING: Call physician or poison control center.
SKIN CONTACT: Wash affected area.
EYE CONTACT: Flush eyes with cool water for at least 15 minutes. Do not let victim rub eyes.
INHALATION: Immediately remove victim to fresh air. Get medical attention immediately.

SECTION 5-PHYSICAL DATA

BOILING POINT: Over 600° F (315° C) at 760 mm Hg pressure
MELTING POINT: -1° C
VAPOR PRESSURE: 0.882 mm Hg at 25° C
SPECIFIC GRAVITY-. 0.882 WmL at 25° C
DIELECTRIC STRENGTH: >56.9
SOLUBILITY IN WATER: Negligible at room temperature.
APPEARANCE AND COLOR: Light yellow to clear and liquid at room temperature.
ODOR: Light vegetable oil odor.

EcoSolvent™ ETI-927

SECTION 6-FIRE AND EXPLOSION HAZARDS

FLASH POINT & METHOD USED: 425°F (218° C)(PMCC)
FLAMMABLE LIMITS: Not applicable.
NFPA RATING: No NFPA rating
HMIS RATING: HEALTH: 0 FIRE: 1 REACTIVITY: 0

SPECIAL FIRE FIGHTING PROCEDURES & PRECAUTIONS

Treat as oil fire. Use water spray, dry chemical, foam or carbon dioxide.

UNUSUAL FIRE & EXPLOSION HAZARDS

Rags soaked with any solvent present a fire hazard and should always be stored in UL listed or Factory Mutual approved, covered containers. Improperly stored rags can create conditions that lead to oxidation. Oxidation, under certain conditions can lead to spontaneous combustion. This product contains antioxidants to retard oxidation.

SECTION 7-REACTIVITY

STABILITY: Stable
HAZARDOUS POLYMERIZATION: None likely
MATERIALS TO AVOID: Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: CO₂, CO
CONDITIONS TO AVOID: None known

SECTION 8-EMPLOYEE PROTECTION

CONTROL MEASURES: Adequate ventilation
RESPIRATORY PROTECTION: None required
PROTECTIVE CLOTHING: No need anticipated
EYE PROTECTION: None required

SECTION 9-ENVIRONMENTAL PROTECTION

ENVIRONMENTAL PRECAUTIONS: Avoid uncontrolled releases of this material into environment.
SPILL OR LEAK PRECAUTIONS: Contain spilled material. Transfer to secure containers. Where necessary, collect using absorbent media.
WASTE DISPOSAL: Dispose of according to federal, state and/or local requirements.

SECTION 10-REGULATORY CONTROLS

DOT CLASSIFICATION: Class 55
DOT PROPER SHIPPING NAME: Cleaning Compound, N.O.S.

SECTION 11-PRECAUTIONS: HANDLING, STORAGE AND USAGE

No special precautions necessary.

SECTION 12-MATERIAL INFORMATION

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The stated MSDS is reliable to the best of the company's knowledge and believed accurate as of the date indicated. However, no representation, warranty or guarantee of any kind, expressed or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.